

## (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



101532646



(43) International Publication Date  
3 June 2004 (03.06.2004)

PCT

(10) International Publication Number  
WO 2004/046682 A2

(51) International Patent Classification<sup>7</sup>:

G01N

(74) Agent: SUCKLING, Andrew; Marks &amp; Clerk, 4220 Nash Court, Oxford Business Park South, Oxford, Oxfordshire OX4 2RU (GB).

(21) International Application Number:

PCT/EP2003/050836

(22) International Filing Date:

14 November 2003 (14.11.2003)

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

0226674.0 15 November 2002 (15.11.2002) GB

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(72) Inventors; and


(75) Inventors/Applicants (for US only): GOUJON, Nicolas [FR/NO]; Agathe Groendahls gt 10, N-0478 Oslo (NO). NAES, Johan, Fredrick [NO/NO]; Smedsvingen 41, N-1395 Hvalstad (NO). VOLDSBEKK, Rune [NO/NO]; 2. Strom Terrasse 44, N-3046 Drammen (NO).

## Published:

— without international search report and to be republished upon receipt of that report

[Continued on next page]

(54) Title: INTEGRATED SEISMIC SENSOR CABLE



WO 2004/046682 A2

(57) Abstract: A seismic cable (110) and a method for producing a seismic cable are disclosed. The seismic cable (110) comprises a sensor module (130); at least one lead (210) to or from the sensor module (130); a stress member (225) extending continuously through the sensor module (130); and a sheath (230) enclosing the leads (210) and the stress member (225), the sheath (230) terminating at each end of the sensor module (130), and at least one mechanical guide (240) in the sensor module (130) deflecting the stress member (230). The method comprises providing a cable core including a stress member (225) and a lead (210); enclosing the cable core in a sheath (230); providing an opening in the sheath (230); and assembling a sensor module (130) to the cable core over the opening such that the stress member (225) extends continuously through the sensor module (130).



*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*